Nail Salon Ultrasonic Cleaner • Autoclaye • Water Distiller



### AGAINST INFECTION AND CROSS CONTAMINATION

The **LABEC USC-5L Ultrasonic Cleaner** is designed for dental practice environments. This unit incorporating Lateral Oscillation Technology that sanitises your needles and other instruments ready for autoclaving. The prepared equipment is polished to a fine finish free from stain, dust, oil, grease and other substances.



Lid	and	Baskets	included
-----	-----	---------	----------

Model	USC-5L
Int. Dim. (mm) L x W x H	240 x 140 x 150
Capacity (Litres)	5
Transducer Power (Watts)	200
Operating Frequency (kHz)	40
Material (interior & exterior)	Stainless steel
Heating	75 Watts / 80°C
Digital Timer (Min)	1 - 99



Laboratory Equipment Pty Ltd email: sales@labec.com.au Ph: 02 9560 2811 • Fax: 02 9560 6131 www.labec.com.au

## **SPECIFICATIONS**

# Nail Salon

Ultrasonic Cleaner • Autoclave • Water Distiller





#### The LABEC STE-8-D Bench Top Autoclave

is a purpose built self contained sterilisation unit. Able to sterilise wrapped and unwrapped solid instruments. Australian TGA approved. Conforms to EN10360/2/4 CE, AS4815. With sterilisation temps 121°C and 134°C. Single pre-vacuum preceding sterilisation. Bowie & Dick test confirmation of steam penetration. Inbuilt printer and included USB memory stick capable to record all batch parameters for QA documentation.

Model	STE-8-D
Int. Dim. (mm) Dia x Depth	170 x 320
Ext. Dim. (mm) W x D x H	420 x 525 x 370
Temp. range	121° or 134°C
Capacity (L)	8
Power (W)	2000
Power Source	10 AMP/ 240 Volt
Controller	LCD Display with adjustable pre-set programs
Printer	Included
Safety Features	Automatic door lock under pressure, safety valve, temperature control and pressure protection system together with a temperature protector mounted on the chamber wall.
Weight (kg)	37





The **LABEC WS1.0 Junior Water Distiller** provides you with high grade distilled water. Use this water for manual cleaning, rinse bath, ultrasonic bath and autoclave water. By not providing pure demineralised water throughout the sanitation and sterilisation process there is a carry over of the salts/minerals and other solids that come through our conventional town water supply. Have you looked inside your kitchen kettle lately?

Model	WS1.0
Distiller Water	1.0 L/Hour
Storage tank (L)	4
Outside Size (mm) W x H x D	320 x 220 x 385
Weight	4.5 kgs
Voltage / Watts	240V / 750W

### DISTILLATE QUALITY

**pH:** 5.4 to 6.0 **Conductivity:** 10 to 20 µS/cm



Laboratory Equipment Pty Ltd email: sales@labec.com.au Ph: 02 9560 2811 • Fax: 02 9560 6131 www.labec.com.au



Laboratory Equipment Pty Ltd