# Glassware Drying Oven (Ambient +5°C to 80°C)

LABEC Glassware Drying Oven is manufactured in Australia with high quality stainless steel for easy maintenance and excellent durability with an acrylic door for easy viewing.

An inconel element inside the chamber and convection heating circulates the warm air inside the chamber providing fast and efficient drying with a cool touch exterior surface.

Available in a range of sizes, suitable for benchtops and general laboratories.

Custom sizes are also available.

## **Temperature**

The ovens are easy to operate with a digital temperature controller and have a temperature range of ambient +5°C to 80°C.

#### **Additional Options**

To suit your requirements the addition of options such as extra shelving, a timer and HEPA filters are also available.

### Standard features include:

- RCD/ELB (earth leakage breaker)
- Stainless Steel Exterior
- Acrylic door panel
- Adjustable/removeable wire shelving





# Glassware Drying Oven (Ambient +5°C to 80°C)

Model	GWD10	GWD14	GWD18	GWD24	GWD36	GWD50
Capacity (L)	16	32	66	160	300	507
Int. Dim. (cm) HxWxD	25 x 25 x 25	35 x 30 x 30	46 x 38 x 38	60 x 50 x 50	90 x 60 x 50	120 x 65 x 65
Ext. Dim. (cm) HxWxD	63 x 38 x 47	73 x 42 x 50	80 x 49 x 58	97 x 63 x 72	128 x 74 x 72	161 x 76 x 83
Temp. Controller	Digital PID Controller					
Temp. Min	Ambient +5°C					
Temp. Max	80°C					
Temp. Setting Accuracy	+/- 5°C					
Temp. Fluctuation	+/- 5°C					
Temp. Sensor	Type K					
Heating System	Electric Element					
Interior Material	Stainless Steel					
Exterior Material	Stainless Steel					
Shelves	2 3					
Options	Timer, additional shelves, HEPA air filters					
Safety Features	Earth leakage breaker (ELB)					
Power Supply	240V/50Hz					
Power (W)	1800 2400					2400
Weight (kg)	20	25	354	45	55	80

